

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0
Revision Date 07/27/2026

Page 1 of 20
Print Date 07/28/2026

SAFETY DATA SHEET

BLACK FOR PVC FG-18**Section 1. Identification**

GHS product identifier : BLACK FOR PVC FG-18
Chemical name : Mixture
CAS number : Mixture
Other means of identification : CC10433413
Product type : solid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **AVIENT CORPORATION**
33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (844) 4AVIENT

Emergency telephone number (with hours of operation) : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture : Not classified.

GHS label elements

Signal word : No signal word.
Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.
Response : Not applicable.
Storage : Not applicable.

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 2 of 20

Print Date 07/28/2026

Disposal : Not applicable.
Hazards not otherwise classified : None known.
Hazards identified when used : No known significant effects or critical hazards.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Chemical name : BLACK FOR PVC FG-18
Other means of identification : BLACK FOR PVC FG-18

Ingredient name	Synonyms	%	Identifiers
Ethene, chloro-, homopolymer	Ethene, chloro-, homopolymer	>= 30 - <= 60	CAS: 9002-86-2
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	>= 7 - <= 13	CAS: 68515-48-0
Limestone	Limestone	>= 5 - <= 10	CAS: 1317-65-3
Carbon black	carbon black non-respirable	>= 3 - <= 7	CAS: 1333-86-4
Chromium oxide	chromium (III) oxide	>= 1 - <= 5	CAS: 1308-38-9
Octadecanoic acid, calcium salt (2:1)	calcium distearate	>= 1 - <= 5	CAS: 1592-23-0
C.I. Pigment Brown 24	chrome antimony titanium buff rutile	>= 1 - <= 5	CAS: 68186-90-3
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate	>= 0.5 - <= 1.5	CAS: 57583-35-4
Quartz (SiO ₂)	crystalline silica, respirable powder	> 0 - <= 1	CAS: 14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures**Description of necessary first aid measures**

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0
Revision Date 07/27/2026

Page 3 of 20
Print Date 07/28/2026

- | | | |
|---------------------|---|--|
| Eye contact | : | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs. |
| Inhalation | : | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. |
| Skin contact | : | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. |
| Ingestion | : | Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. |

Most important symptoms/effects, acute and delayed**Potential acute health effects**

- | | | |
|---------------------|---|---|
| Eye contact | : | No known significant effects or critical hazards. |
| Inhalation | : | No known significant effects or critical hazards. |
| Skin contact | : | No known significant effects or critical hazards. |
| Ingestion | : | No known significant effects or critical hazards. |

Over-exposure signs/symptoms

- | | | |
|---------------------|---|-------------------|
| Eye contact | : | No specific data. |
| Inhalation | : | No specific data. |
| Skin contact | : | No specific data. |
| Ingestion | : | No specific data. |

Indication of immediate medical attention and special treatment needed, if necessary

- | | | |
|-----------------------------------|---|---|
| Notes to physician | : | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : | No specific treatment. |
| Protection of first-aiders | : | No action shall be taken involving any personal risk or without suitable training. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures**Extinguishing media**

- | | | |
|-------------------------------------|---|---|
| Suitable extinguishing media | : | In case of fire, use water spray (fog), foam, dry chemical or CO ₂ . |
|-------------------------------------|---|---|

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0
Revision Date 07/27/2026

Page 4 of 20
Print Date 07/28/2026

- Unsuitable extinguishing media** : None known.
- Specific hazards arising from the chemical** : No specific fire or explosion hazard.
- Hazardous thermal decomposition products** : May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials: carbon dioxide, carbon monoxide, halogenated compounds, metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 5 of 20

Print Date 07/28/2026

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters**Occupational exposure limits**

Ingredient name	Exposure limits
Ethene, chloro-, homopolymer	ACGIH TLV (2008-01-01). [Polyvinyl chloride] A4. TWA 8 hours: 1 mg/m ³ Form: Respirable fraction
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	None.
Limestone	CAL OSHA PEL (2018-05-16). [limestone] TWA 8 hours: 10 mg/m ³ Form: Total dust TWA 8 hours: 5 mg/m ³ Form: Respirable fraction OSHA PEL 1989 (1989-03-01). [Calcium carbonate] TWA 8 hours: 5 mg/m ³ Form: Respirable fraction TWA 8 hours: 15 mg/m ³ Form: Total dust OSHA PEL 1989 (1989-03-01). [Limestone] TWA 8 hours: 5 mg/m ³ Form: Respirable fraction TWA 8 hours: 15 mg/m ³ Form: Total dust OSHA PEL 1989 (1989-03-01). [Marble] TWA 8 hours: 5 mg/m ³ Form: Respirable fraction TWA 8 hours: 15 mg/m ³ Form: Total dust OSHA PEL (1993-06-30). [Calcium Carbonate] TWA 8 hours: 5 mg/m ³ Form: Respirable fraction

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Page 6 of 20

Revision Date 07/27/2026

Print Date 07/28/2026

	TWA 8 hours: 15 mg/m³ Form: Total dust NIOSH REL (2015-02-13). [calcium carbonate] TWA 10 hours: 10 mg/m³ Form: Total TWA 10 hours: 5 mg/m³ Form: Respirable fraction
Carbon black	CAL OSHA PEL (2018-05-16). [carbon black] TWA 8 hours: 3.5 mg/m³ ACGIH TLV (2010-12-06). [Carbon black] A3. TWA 8 hours: 3 mg/m³ Form: Inhalable fraction NIOSH REL (2010-09-01). [carbon black] See Appendix A - NIOSH Potential Occupational Carcinogen. TWA 10 hours: 0.1 mg/m³ (as cyclohexane-extractable fraction) TWA 10 hours: 3.5 mg/m³ OSHA PEL 1989 (1989-03-01). [Carbon black] TWA 8 hours: 3.5 mg/m³ OSHA PEL (1993-06-30). [Carbon black] TWA 8 hours: 3.5 mg/m³
Chromium oxide	OSHA PEL (1993-06-30). [Chromium metal and insol salts (as Cr)] TWA 8 hours: 1 mg/m³ (as Cr) OSHA PEL (1993-06-30). [Chromium (III) compounds (as Cr)] TWA 8 hours: 0.5 mg/m³ (as Cr) NIOSH REL (2010-09-01). [chromium (III) compounds as Cr] TWA 8 hours: 0.5 mg/m³ (as Cr) CAL OSHA PEL (2018-05-16). [chromium (iii) compounds as Cr] TWA 8 hours: 0.5 mg/m³ (as Cr) OSHA PEL 1989 (1989-03-01). [Chromium metal and insoluble salts] TWA 8 hours: 1 mg/m³ OSHA PEL 1989 (1989-03-01). [Chromium (III) compounds (as Cr)] TWA 8 hours: 0.5 mg/m³ (as Cr) ACGIH TLV (2018-03-20). [inorganic chromium III compounds as Cr] A4. TWA 8 hours: 0.003 mg/m³ (as Cr) Form: Inhalable fraction
Octadecanoic acid, calcium salt (2:1)	CAL OSHA PEL (2018-05-16). [stearates] TWA 8 hours: 10 mg/m³ ACGIH TLV (2017-03-01). [Stearates] A4. TWA 8 hours: 10 mg/m³ Form: Inhalable fraction TWA 8 hours: 3 mg/m³ Form: Respirable fraction
C.I. Pigment Brown 24	OSHA PEL (1993-06-30). [Antimony and compounds (as Sb)]

SAFETY DATA SHEET

BLACK FOR PVC FG-18

Version Number 1.0

Page 7 of 20

Revision Date 07/27/2026

Print Date 07/28/2026

	TWA 8 hours: 0.5 mg/m³ (as Sb) OSHA PEL (1993-06-30). [Chromium (III) compounds (as Cr)] TWA 8 hours: 0.5 mg/m³ (as Cr) NIOSH REL (2010-09-01). [chromium (III) compounds as Cr] TWA 8 hours: 0.5 mg/m³ (as Cr) NIOSH REL (2010-09-01). [antimony] TWA 10 hours: 0.5 mg/m³ CAL OSHA PEL (2018-05-16). [antimony and compounds as Sb] TWA 8 hours: 0.5 mg/m³ (as Sb) CAL OSHA PEL (2018-05-16). [chromium (iii) compounds as Cr] TWA 8 hours: 0.5 mg/m³ (as Cr) OSHA PEL 1989 (1989-03-01). [Antimony and compounds (as Sb)] TWA 8 hours: 0.5 mg/m³ (as Sb) OSHA PEL 1989 (1989-03-01). [Chromium (III) compounds (as Cr)] TWA 8 hours: 0.5 mg/m³ (as Cr) ACGIH TLV (1994-09-01). [Antimony and compounds as Sb] TWA 8 hours: 0.5 mg/m³ (as Sb) ACGIH TLV (2018-03-20). [inorganic chromium III compounds as Cr] A4. TWA 8 hours: 0.003 mg/m³ (as Cr) Form: Inhalable fraction
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	OSHA PEL (1993-06-30). [Tin, organic compounds (as Sn)] TWA 8 hours: 0.1 mg/m³ (as Sn) NIOSH REL (2010-09-01). [tin organic compounds as Sn] Absorbed through skin. TWA 10 hours: 0.1 mg/m³ (as Sn) CAL OSHA PEL (2018-05-16). [tin, organic compounds as Sn] Absorbed through skin. STEL 15 minutes: 0.2 mg/m³ (as Sn) TWA 8 hours: 0.1 mg/m³ (as Sn) OSHA PEL 1989 (1989-03-01). [Tin, organic compounds (as Sn)] Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn) Form: Organic. ACGIH TLV (2012-03-05). [Tin, organic compounds as Sn] A4. Absorbed through skin. TWA 8 hours: 0.1 mg/m³ (as Sn) STEL 15 minutes: 0.2 mg/m³ (as Sn)
Quartz (SiO ₂)	OSHA PEL Z3 (1997-09-03). [Silica, Crystalline Quartz non-respirable] TWA 8 Hours: 30/ (%SiO₂+2) mg/m³ Form: Total dust OSHA PEL Z3 (2016-06-23). [Silica, Crystalline Quartz respirable powder]

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 8 of 20

Print Date 07/28/2026

	TWA 8 Hours: 10/ (%SiO₂+2) mg/m³ Form: Respirable TWA 8 Hours: 250/ (%SiO₂+5) mppcf Form: Respirable CAL OSHA PEL (2018-05-16). [silica, crystalline - quartz] TWA 8 hours: 0.05 mg/m³ OSHA PEL 1989 (1989-03-01). [Silica, crystalline quartz (as quartz), respirable dust] TWA 8 hours: 0.1 mg/m³ (Calculated as Quartz) Form: Respirable dust OSHA PEL (2016-06-23). [Silica, crystalline] TWA 8 hours: 50 µg/m³ Form: Respirable dust NIOSH REL (2010-09-01). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)] See Appendix A - NIOSH Potential Occupational Carcinogen. TWA 10 hours: 0.05 mg/m³ Form: Respirable dust ACGIH TLV (2005-12-09). [Silica, crystalline] A2. TWA 8 hours: 0.025 mg/m³ Form: Respirable fraction
--	---

Biological exposure indices

No exposure indices known.

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 9 of 20

Print Date 07/28/2026

Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties
--

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	solid [Pellets.]
Color	:	BLACK
Odor	:	Not available.
Odor threshold	:	Not available.
pH	:	Not available.
Melting point/freezing point	:	Not available.
Boiling point or initial boiling point and boiling range	:	Not available.
Flash point	:	Not applicable.
Evaporation rate	:	Not available.
Flammability	:	Not available.
Lower and upper explosion limit/flammability limit	:	Lower: Not applicable. Upper: Not applicable.
Vapor pressure	:	Not available.
Relative vapor density	:	Not applicable.
Relative density	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-octanol/water	:	Not applicable.
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	Not available.

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0
Revision Date 07/27/2026

Page 10 of 20
Print Date 07/28/2026

Viscosity : **Dynamic** : Not available.
Kinematic : Not available.

Particle characteristics

Median particle size : Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers during processing.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information**Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Rat - Oral - LD50 10,000 mg/kg
Carbon black	Rat - Oral - LD50 15,400 mg/kg
Octadecanoic acid, calcium salt (2:1)	Rat - Oral - LD50 10,000 mg/kg

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0
Revision Date 07/27/2026

Page 11 of 20
Print Date 07/28/2026

--	--

Conclusion/Summary : Mixture.Not fully tested.

Skin corrosion/irritation

Conclusion/Summary : Mixture.Not fully tested.

Serious eye damage/eye irritation

Product/ingredient name	Result
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Rabbit - Eyes - Mild irritant

Conclusion/Summary : Mixture.Not fully tested.

Respiratory corrosion/irritation

Conclusion/Summary : Mixture.Not fully tested.

Respiratory or skin sensitization**Skin**

Conclusion/Summary : Mixture.Not fully tested.

Respiratory

Conclusion/Summary : Mixture.Not fully tested.

Germ cell mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
-------------------------	------	------	-----

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Page 12 of 20

Revision Date 07/27/2026

Print Date 07/28/2026

Ethene, chloro-, homopolymer	-	3	-
Carbon black	-	2B	-
Chromium oxide	-	3	-
Octadecanoic acid, calcium salt (2:1)	-	-	-
C.I. Pigment Brown 24	-	3	-
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	-	-	-
Quartz (SiO ₂)	+	1	Known to be a human carcinogen.

Reproductive toxicity

Conclusion/Summary : Mixture. Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Result
Quartz (SiO ₂)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 13 of 20

Print Date 07/28/2026

Skin contact : No specific data.
 Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects : Not available.
 Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
 Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Mixture. Not fully tested.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	10000 mg/kg	N/A	N/A	N/A	N/A
Carbon black	15400 mg/kg	N/A	N/A	N/A	N/A
Octadecanoic acid, calcium salt (2:1)	10000 mg/kg	N/A	N/A	N/A	N/A

Section 12. Ecological information

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0
Revision Date 07/27/2026

Page 14 of 20
Print Date 07/28/2026

Toxicity

Product/ingredient name	Result
BLACK FOR PVC FG-18	Remarks: Chemicals are not readily available as they are bound within the polymer matrix.
Carbon black	Acute EC50 Fresh water Daphnia - <i>Daphnia magna</i> 37.563 Mg/l [48 h]

Conclusion/Summary : Not available.

Persistence and degradability

Not available.

Conclusion/Summary : Chemicals are not readily available as they are bound within the polymer matrix.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	8.8	3.00	Low

Mobility in soil

Soil/Water partition coefficient : Not available.
Mobility : Chemicals are not readily available as they are bound within the polymer matrix.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 15 of 20

Print Date 07/28/2026

requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

U.S.DOT 49CFR : Not regulated for transportation.
Ground/Air/Water

IATA : Consult mode specific transport rules

IMDG : Consult mode specific transport rules

Section 15. Regulatory information**U.S. Federal regulations**

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

TSCA 12(b) - Chemical export notification

Clean Air Act Section 112(b) : Listed
Hazardous Air Pollutants (HAPs)
Clean Air Act Section 602 Class I : Not listed
Substances
Clean Air Act Section 602 Class : Not listed
II Substances
DEA List I Chemicals (Precursor : Not listed
Chemicals)
DEA List II Chemicals (Essential : Not listed
Chemicals)

SARA 302/304**Composition/information on ingredients**

No products were found.

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 16 of 20

Print Date 07/28/2026

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

No products were found.

Name	%	Classification
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	$\geq 7 - \leq 13$	EYE IRRITATION - Category 2B
Quartz (SiO ₂)	$> 0 - \leq 1$	CARCINOGENICITY - inhalation - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

SARA 313**Form R - Reporting requirements**

Product name	CAS number	%
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	68515-48-0	$\geq 7 - \leq 13$
Chromium oxide	1308-38-9	$\geq 1 - \leq 5$
C.I. Pigment Brown 24	68186-90-3	$\geq 1 - \leq 5$

Supplier notification

Product name	CAS number	%
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	68515-48-0	$\geq 7 - \leq 13$
Chromium oxide	1308-38-9	$\geq 1 - \leq 5$
C.I. Pigment Brown 24	68186-90-3	$\geq 1 - \leq 5$

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed:
Limestone

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 17 of 20

Print Date 07/28/2026

Carbon black
Chromium oxide**New York** : None of the components are listed.

New Jersey : The following components are listed:
 PVC
 CALCIUM CARBONATE
 CARBON BLACK
 CHROMIC OXIDE
 ANTIMONY compoundsCHROMIUM
 COMPOUNDSCHROMIUM III COMPOUNDS
 SILICA, QUARTZ

Pennsylvania : The following components are listed:
 LIMESTONE
 CARBON BLACK
 CHROMIUM COMPOUNDS
 ANTIMONY COMPOUNDSCHROMIUM COMPOUNDS

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich, Carbon black, Quartz, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	Yes.	-
Carbon black	-	-
Quartz	-	-

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals****Chemical Weapons Convention List Schedule I Chemicals**

None of the components are listed.

Chemical Weapons Convention List Schedule II Chemicals

None of the components are listed.

SAFETY DATA SHEET

BLACK FOR PVC FG-18

Version Number 1.0

Revision Date 07/27/2026

Page 18 of 20

Print Date 07/28/2026

Chemical Weapons Convention List Schedule III Chemicals

None of the components are listed.

Montreal Protocol

None of the components are listed.

Stockholm Convention on Persistent Organic Pollutants

Annex A - Elimination - Production

None of the components are listed.

Annex A - Elimination - Use

None of the components are listed.

Annex B - Restriction - Production

None of the components are listed.

Annex B - Restriction - Use

None of the components are listed.

Annex C - Unintentional - Production

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Rotterdam Convention on Prior Informed Consent (PIC) - Industrial

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC) - Pesticide

None of the components are listed.

Rotterdam Convention on Prior Informed Consent (PIC) - Severely hazardous pesticide

None of the components are listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Heavy metals - Annex 1

None of the components are listed.

POPs - Annex 1 - Production

None of the components are listed.

POPs - Annex 1 - Use

None of the components are listed.

POPs - Annex 2

SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 19 of 20

Print Date 07/28/2026

None of the components are listed.

POPs - Annex 3

None of the components are listed.

Inventory list

Australia	:	Not determined.
Canada	:	At least one component is not listed in DSL but all such components are listed in NDSL.
China	:	Not determined.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	All components are active or exempted.
Viet Nam	:	Not determined.

Section 16. Other information**Hazardous Material Information System (U.S.A.)**

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)**Flammability**


SAFETY DATA SHEET**BLACK FOR PVC FG-18**

Version Number 1.0

Revision Date 07/27/2026

Page 20 of 20

Print Date 07/28/2026

**Procedure used to derive the classification**

Not classified.

History

Date of printing : 07/28/2026
Date of issue/Date of revision : 07/27/2026
Date of previous issue : 00/00/0000
Version : 1.0
Prepared by : GHATES
Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 DOT = Department of Transportation
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 IMO = International Maritime Organization
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 N/A = Not available
 SGG = Segregation Group
 TDG = Transportation of Dangerous Goods
 UN = United Nations

References**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.